ЛЛХ

Baseline product line

Hub 2 (4G) Jeweller

Security system control panel with 3 communication channels: Ethernet and 2 SIM cards (4G). Supports photo verification provided by detectors of the MotionCam series.











Integration with third-party CCTV cameras or DVRs



Informing users with push notifications, calls, and SMS

Always online

To guarantee timely alarm transmission to the security company and users, Hub 2 supports connection to three Internet providers simultaneously: via **Ethernet** and **two 4G SIM cards**. Communication channels operate in parallel, and automatic switching between them takes seconds.

In-app control and configuration

Hub is connected to Ajax apps, security companies, and users via a secure channel through the Ajax Cloud server located in several AWS data centres. Server availability is 99.99%.

Intuitive Ajax apps provide remote configuration and all information about system devices from anywhere the Internet is available, on a smartphone or PC. An installer can remotely change the settings and provide services in time – no need to visit the object.



Guaranteed delivery of alarms and photos

An Ajax system uses two-way secure radio communication based on Jeweller and Wings proprietary protocols. Radio protocols work

in parallel and focus on their function, guaranteeing instant data delivery despite weak signal and communication interruptions.



Encrypted two-way radio communication



Frequency hopping against radio interference and signal interception



Automatic power adjustment of radio transmitters

Notifications about jamming and connection loss

Jeweller \forall

Jeweller transmits alarms, events, and all readings

- Up to 2,000 m of radio communication in an open space
- Encryption and device authentication to prevent spoofing
- Regular polling to display current devices' statuses

Wings

Wings transmits photos and large data packages

- Up to 1,700 m of radio communication in an open space
- Unique uploading algorithm and data delivery confirmation
- Data backup and resend in case of transmission interruptions

Sabotage-resistant



Built-in backup battery giving up to 16 hours of autonomous operation



Detecting loss of connection with devices in 36 seconds



Detecting loss of connection with Ajax Cloud in 1 minute



Superior, Fibra, and Baseline product lines are mutually compatible. This opens up numerous possibilities for building systems of any configuration.

| Compliance with standards | Communication with Ajax devices | External communication channels | Features |
|------------------------------------|--------------------------------------|---|---|
| EN 50131 (Grade 2) PD 6662:2017 | Jeweller communication technology | Ethernet 8P8C slot Up to 100 Mb/s | 50 users 50 rooms 32 automation scenarios |
| | Wings communication technology | Cellular network | 25 cameras or DVRs 9 security groups |

| | Frequency bands 866.0-866.5 MHz 868.0-868.6 MHz 868.7-869.2 MHz 905.0-926.5 MHz 915.85-926.5 MHz 921.0-922.0 MHz Depends on the sales region Jeweller communication range up to 2,000 m In an open space Wings communication range up to 1,700 m In an open space | 2 slots for micro-SIM 2G (GSM900/DCS1800 (B3/B8)) 3G (WCDMA 850/900/2100 (B1/B5/B8)) 4G/LTE (FDD B1/B3/B5/B7/B8/B20) | |
|-------------------|--|--|---------------------|
| Power supply | Installation | Enclosure | Complete set |
| Main power supply | Operating temperature range | Colour | Hub 2 (4G) Jeweller |

| 100-240 V~, 50/60 Hz | from -10°C to +40°C | black, white | Power cable |
|--------------------------------|---------------------------|-------------------|-----------------------------|
| | | | Ethernet cable |
| Backup power supply | Operating humidity | Dimensions | SIM card |
| built-in Li-Ion battery, 2 A·h | up to 75% | 163 × 163 × 36 mm | Depends on the sales region |
| Up to 16 hours of autonomous | | | Installation kit |
| operation | Protection class | Weight | Quick start guide |
| | IP20 | 362 g | |
| | | | |



Find detailed information by the link:

ajax.systems/support/devices/hub-2-4g

- \sim support@ajax.systems
- @AjaxSystemsSupport_Bot

