

# **AU-X2IPRO-DA**

# **DANTE 2-CHANNEL XLR INPUT ADAPTER**

The AU-X2IPRO-DA from TiGHT AV effortlessly integrates two channels of analog audio into your Dante network. Utilizing Audinate's original Dante Ultimo chip, the unit supports sample rates up to 96kHz.

Featuring an installer-friendly interface equipped with phoenix analog connectors, input sensitivity settings via dip switch, a reset button, and a rugged metal housing, the AU-X2IPRO-DA offers simplicity and cost-efficiency. It provides a straightforward solution for seamlessly connecting analog equipment to a Dante network in professional installations.

For simplified setup, PoE support enables easy installation using a PoE-capable network switch or a separate power supply. Additionally, optional Phoenix to XLR cables are available, offering increased connectivity options.



# **KEY FEATURES**

- Plug and Play
- · 2 audio inputs with selectable sensitivity per input
- Dante and AES67 support
- 24-bit audio support
- Supports 802.3af PoE
- Dante Controller and Dante Domain Manager compatible
- Install friendly
- Optional local power
- Rugged metal housing
- Mounting ears
- Reset button

## **SPECIFICATIONS**

#### AUDIO

Max input level (balanced):	+24 dBu / +4 dBu / 0 dBu/ 0 dBV /-10 dBV
Frequency Response:	20Hz to 20kHz (-/+0.5dB)
Impedance:	7.2k $\Omega$ (balanced) or 3.6k $\Omega$ (unbalanced)
Dynamic Range:	>100 dB
Signal to Noise Ratio:	>100 dB
THD:	<0.01% @+4 dBu

### DANTE

Sample Rate:	44.1kHz, 48kHz, 96kHz
Bit Depth:	24
Dante Device Latency:	1, 2 or 5ms (configurable using Dante Controller)
Network Transport:	Dante Audio over IP
	AES67 BTP

#### GENERAL

021121012	
Operation Temperature:	-5°C to +55°C (+23°F to +131°F)
Storage Temperature:	-25°C to +70°C (-13°F to +158°F)
Power:	802.3af PoE or 12V DC
Power Consumption:	2.65W (Max)
Dimension (W x H x D):	128 x 26 x 48 mm
Net Weight:	195g
Compliance:	FCC, CE
Environmental:	RoHS, REACH, WEEE

#### PACKAGE LIST

•1 x AU-X2IPRO-DA

•1 x Mounting ears (attached by default)

1 x User Manual

5

YEAR

6

MONTH

ADVANCE

**OPTIONAL ACCESSORIES** 

ALI-X2IPBO-2XM: Pre-terminated Phoenix to XLB cable

SP-PSU-DC12V1A-EU/UK/US: 12V1A Power Adapter

#### WARRANTY

• 5 Years limited warranty with 6 month advance replacement.

# **TiGHT POLICY**

### Faulty product - minimal down time.

Up until six months after purchase, TiGHT AV will replace your product in advance of return of faulty product.

### Your investment - built to last.

All TiGHT AV products come with a five year limited warranty.

