

HuddleCamHD

Compatibility

- VISCA Protocol
- PELCO-D
- PELCO-P

What's in the box?

- Three-Axis Joystick
- RS232 cable
- DC12V Power Supply
- User Manual

Features

- Durable Metal Housing
- RS232, RS485, & RS422
- On Screen Display Menu control
- Variable Pan, Tilt, Zoom, & Focus speed control
- Iris, Focus, & Preset control
- 6) Camera Quick Select keys
- 9) Quick Preset Set & Call keys

Model Number: HC-JOY-G3

Easy pan, tilt, & zoom control for any VISCA or PELCO protocol camera!
Adjust pan, tilt, zoom, & focus speeds.
Use 3-dimensional joystick with "twist" for zoom control



1. LCD Display

Menu options are displayed here

2. Lens Control

Focus+/-, Focus Lock/Unlock, Iris +/-, Auto Focus & Exposure

3. Joystick

Three-axis joystick controller

4. Camera Quick Select

Quickly swap between first 6 cameras

5. Preset & OSD Control

Allows for preset, speed, & OSD control

6. Numeric Keys

Numeric keys for presets, changing parameters, and more

7. DB9 Connection

Allows for RS232 through DB9 connections

8. Phoenix Connection

Allows for RS422 or RS485 wiring connections

9. Power Connection

DC12V Power Connection





















Key Technical Specifications

Connections:	RS232, RS485, RS422
Baud Rate:	1200-19200 bps
Interfaces:	DB9: RS232; 5SCT: RS485/RS422
Max Cameras:	Control up to 255 Cameras
Max Presets:	Up to 255 Presets
Max Distance:	3,937' (1200m) using 24 gauge twisted pair




Operation Specifications

Power:	6W (12VDC Voltage)
Working Temp:	14° ~ 122°F (-10° ~ +50°C)
Working Humidity:	10 ~ 90% (non-condensation)
Weight:	3.4 lbs 1.6 kg
Dimensions (in.):	12.6W x 4.3H x 7.1D
Dimensions (mm.):	320W x 109H x 180D









Camera Line

	HC-GO-BK		HC-GO-WH	USB-powered, 110° HFOV, all-in-one Camera, Mic, & Speakerphone
	HC3X-BK-G2		HC3X-WH-G2	3X optical zoom, 74° HFOV, USB 2.0 video up to 1080p-30
	HC3XA-BK		HC3XA-WH	3X opt zoom w/ built in mic array, 74° HFOV USB 2.0 video up to 1080p-30
	HC3XW-GY-G2		HC3XW-WH-G2	3X Wide optical zoom, 90° HFOV, USB 3.0 video up to 1080p-30
	HC10X-720-BK		HC10X-720-WH	10X optical zoom, 57° HFOV, USB 2.0 video up to 1080p-30
	HC10XA-BK		HC10XA-WH	10X opt zoom w/ built in mic array, 57° HFOV USB 2.0 video up to 1080p-30
	HC10X-GY-G3		HC10X-WH-G3	10X optical zoom, 61° HFOV, USB 3.0 video up to 1080p-30
	HC20X-GY-G2		HC20X-WH-G2	20X optical zoom, 58° HFOV, USB 3.0 video up to 1080p-30
	HC30X-GY-G2		HC30X-WH-G2	30X optical zoom, 63° HFOV, USB 3.0 video up to 1080p-30
	HC-SIMPLTRACK-TP		HC-SIMPLTRACK-CM	20X optical zoom, 59° HFOV, Auto tracking camera w/ video up to 1080p-60





Control Accessories

	HC-JOY-G2			RS232, RS485, & RS422 3D joystick, VISCA, Pelco-P, Pelco-D
	DB9M-F-xx		VISCA-xx	VISCA RS232 Plenum cable, 4 lengths shown in ft. (xx=25, 50, 75, 100)

Mounting Accessories

	HCM-1-BK		HCM-1-WH	Small Wall Mount, mounts directly to wall or box with supplied hardware
	HCM-2-BK		HCM-2-WH	Large Wall Mount, mounts directly to wall or box with supplied hardware
	HCM-1C-WH		HCM-2C-WH	Small/Large open ceiling mount, mounts to 1" NPT pipe
	PT-CM-1-BK		PT-CM-1-WH	Surface Ceiling Mount, mounts directly to ceiling or box w/ supplied hardware

Conference Audio

	HP-AIR-BK		HP-AIR-WH	Wireless Speakerphone with USB receiver
	HP-AIR-BA-BK			Wireless Speakerphone with USB receiver and external amplifier feed
	HP-AIR2-DUO			Dual Wireless Speakerphones with USB receiver

