

RP6503

Pro Series













MeetingroomCare* protects users' health and vision: The certified germ-resistant coating is applied on the front ports, pens, remote controls, and screens. Plus, RP03 delivers optimal colour performance thanks to its low blue light feature, which makes it the world's first interactive display approved by Eyesafe®.



With the built-in air quality sensor and air ioniser, meeting rooms can both be monitored for pollutant particles and cleansed by negative ions that are released automatically or remotely via DMS.



With the **dedicated USB port for cameras**, RP03 Series allows remote participants to see every attendee in the meeting room during video conferencing.

Panel	Screen size		65"
	Resolution		4K UHD 3840 × 2160
	Brightness (typ.)		350 nits
	Contrast ratio (typ.)		1200 : 1
	Dynamic contrast ratio		30,000 : 1
	Viewing angle (H/V)		178°
	Response time (G-t-G)		8 ms
	Backlight life (hrs)		50,000
	Panel surface		AG, Haze 25%
	Operating hours		18 hours / 7 days
	Orientation		Landscape
Platform solution	System memory		8 GB
	Storage		64 GB
	os		Android 11
	Power supply		100-240 V 50/60 Hz
	. J. J. Juppiy	Maximum (W/h)	411
	Power consumption	Typical (W/h)	80
		Standby mode (W/h)	<0.5
	AC power switch		Yes
	•		
	Wake up		LAN / HDMI / VGA / DP
Touch	Technology		Fine IR Plus
	Number of touch points		40
	Interface		USB Type B x 3
Glass	Tempered glass		3.2 mm
	Hardness		9H
	AG coating		Yes
MeetingroomCare* Technology	Smart Eye-Care solution		Flicker-free & Low blue light (TÜV & Eyesafe® certified)
	Air quality sensor		CO ₂ - PM _{2.5} - PM ₁₀ , Temperature & Humidity, Air ioniser
	Germ-resistant screen		Yes (TÜV & SIAA certified)
Environment	Operation temperature		0°C ~ 40°C
	Operating humidity		20% ~ 80% RH non-condensing
	Energy efficiency		Energy Star 8.0 certified
Connectivity	Input		VGA x 1, HDMI 2.0 x 3, DP 1.2a x 1, Audio (3.5 mm) x 1
	Output		HDMI 2.0 x 1, Audio (3.5 mm) x 1
	USB		Type A x 7 (2.0 x 2 / 3.2 Gen 1 x 5), Type B x 3 (3.0), Type C x 2 (3.0)
	RS232		x 1
	RJ45 (LAN)		x 2 (Android / OPS) up to 1000Mbps
	Remote controller		x 1
	Built-in speaker		2 x 16 W / 1 x Subwoofer 16 W
Audio	Dolby Audio		Yes
	Array microphones		x 8
Mechanical	Dimension (mm)		1489.3 × 934.3 × 121.5
	Difficultion (IIIII)	Net weight	43
	Weight (kg)	Gross weight	56
	Bezel width (mm		16.6 / 16.6 / 16.6 / 16.6
	Wall mounting (VESA)		
	(screw type / max. length)		600 × 400 (4 × M8 × 25L)
	Wall mount kit		Included
	OPS slot		Yes
			Yes (supports single sign-on with Azure
	NFC sensor		Active Directory and Google Workspace)
Pen tray			Yes
Warranty			3-year warranty on-site exchange

BenQ TEY21 series OPS slot-in PC is certified by Microsoft Azure IoT
PRO2 with TEY21 series is certified by Intel® Market Ready Solutions.

Registered trademark as ClassroomCare®

[→] Specifications subject to change without notice

SOFTWARE



EZWrite 6

Open Microsoft documents and image files directly on the display, and save sessions in editable whiteboard files (IWB) with Cloud Whiteboarding.



InstaShare 2



X-Sign Broadcast

Announcement system for instant messaging and group notification. Send visual alerts, warnings, videos to all or one specific device.























NFC SENSOR & KEYPAD BUTTONS














CAMERA USB PORT, WIFI DONGLE &





USB3.0

DOWN I/O

















SIDE I/O
















USB3.0



DIMENSIONS (MM)







Benq

