

# InstaShow® VS20

## Wireless Video Conferencing System

### Smooth Collaboration in Hybrid Meetings

VS20 is the ultimate wireless presentation and video conferencing device with 4K video output, embedded microphone, and intuitive features such as touchback and extended screen, perfect for high-quality and collaborative hybrid meetings.

### Hassle-free IT Management

Ease the burden of IT management with VS20, featuring a user-friendly web interface and secure data management through WPA2 encryption, leaving you free from any IT headaches.



The BenQ VS20 system offers seamless **plug-and-play screen sharing** during meetings, with the option to install advanced BenQ software and make use of features that facilitate hybrid video conferences.



The VS20 video conferencing solution boasts a unique **built-in microphone** button and the ability to configure an **external camera** for flexible video source options.



The **switchable dual interface** allows for easy switching between USB Type-C or Type-A cables for the button.



Versatile and flexible, the VS20 is ideal for meetings of any size, from small huddle rooms to large boardrooms, thanks to its extensive **20-metre transmission distance**.



VS20 fully supports **BYOM** with Windows devices, allowing users to bring their own device and preferred conferencing solution to host a video conference.



**BenQ**

## TECHNICAL SPECIFICATIONS

| General                   |                                                                                                                                                                                           |
|---------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Model Name                | VS20                                                                                                                                                                                      |
| Interface                 | USB Type-C (With one spare cable: USB Type-A and HDMI)                                                                                                                                    |
| Input Resolution          | Up to 4k @30fps                                                                                                                                                                           |
| Output Resolution         | Up to 4k @60fps                                                                                                                                                                           |
| Split Mode                | 4 split mode (on/off)                                                                                                                                                                     |
| Simultaneous Connections  | 32 pcs                                                                                                                                                                                    |
| Wi-Fi Standard            | IEEE 802.11ac, 5GHz, 2T2R, IEEE 802.11n, 2.4GHz 5GHz , 2T2R                                                                                                                               |
| Maximum Data Rate         | Up to 867 Mbps                                                                                                                                                                            |
| Frequency Band            | 2.4GHz, 5GHz                                                                                                                                                                              |
| Wi-Fi Authentication      | WPA2 AES 128bit / WPA2 enterprise 256bit                                                                                                                                                  |
| WAN                       | 1 Gbps                                                                                                                                                                                    |
| Supported Platform (BYOM) | Windows                                                                                                                                                                                   |
| Supported Mobile Display  | Airplay, MiraCast                                                                                                                                                                         |
| Environmental             |                                                                                                                                                                                           |
| Reach Distance            | Max. 20m                                                                                                                                                                                  |
| Power Consumption         | Receiver: 11W/36W (Typical/Max)                                                                                                                                                           |
| Standby Power Consumption | <0.5W                                                                                                                                                                                     |
| Weight (Net)              | 530g (Receiver x1 + Button x2)                                                                                                                                                            |
| Operating Temperature     | 0°C to 40°C                                                                                                                                                                               |
| Others                    |                                                                                                                                                                                           |
| Vulnerability Test        | No vulnerability risk                                                                                                                                                                     |
| OSD Language              | Czech/Danish/German/English/European Spanish/Finnish/European French/Italian/Japanese/Korean/Norwegian/Polish/Brazilian Portuguese/Russian/Swedish/Simplified Chinese/Traditional Chinese |
| Accessory                 | Receiver x1, Button x2, Cradle x1, Antenna x4, Power adapter x1, Quick start guide x1, Spare cable x1 (USB Type-A and HDMI)                                                               |
| Part Number               | 9H.JRS78.NIE                                                                                                                                                                              |
| EAN Code                  | 471 8755 08888 9                                                                                                                                                                          |



## DIMENSIONS & CONNECTIVITY



\*Units in mm



[benq.eu/en-eu/business/wireless-presentation.html](https://benq.eu/en-eu/business/wireless-presentation.html)

**BenQ**

© 2023 BenQ Corp. Specifications may vary by region, please visit your local stores for details. Actual product's features and specifications are subject to change without notice. This material may include corporate names and trademarks of third parties, which are the properties of the third parties respectively.