

## Video Intercom Reader Pro

The Openpath Video Intercom Reader Pro combines a built-in high resolution camera, intelligent intercom, and multi-technology reader into a slim and sleek form factor. Visitors use the intercom to initiate calls, communicate with assigned users, and are visually identified within the Openpath app. Automatically associate video footage with access events and visually monitor entries in the Openpath Control Center. The Video Intercom Reader Pro is a multi-technology reader that supports both low (125 kHz) and high (13.56 MHz) frequencies. The camera angle is adjustable during installation, ensuring optimal video footage.



### Features

#### Works with any System

Easily integrates with legacy access control systems, logical software systems, and existing video systems via ONVIF-compliant platform

#### Touchless Reliable Access

Our patented Triple Unlock technology supports hands-free supports hands-free Wave to Unlock, mobile or watch app, tablet, HF and LF keycards, fobs, and Cloud Key

#### Video at the Door

Associate video with access events or alerts and visually monitor entries from the app or Control Center

#### Smart Intercom

Visitors can tell the Video Intercom Reader Pro the name of the person they're visiting, ask to speak to a receptionist, or leave a voicemail, all via the intercom's intelligent voice interface

#### Clear Calls

Two-way audio streaming with echo and noise cancellation lets you easily communicate with guests at the door

#### Easy to Install

Sleek mullion form factor is easy to mount and install with simple PoE connectivity and snap-in design

#### Cloud Security

Encrypted end-to-end communication, strong public key cryptography

#### Interoperability

Easily integrates with physical on-premise systems and logical software systems

#### Capacity Tracking

Track occupancy and enforce capacity limits with innovative BLE functionality

#### Monitoring

Built-in diagnostic and real-time troubleshooting insights



### Choose your way in



## Video Intercom Reader Pro

### Card Compatibility

- Openpath DESFire EV3
- MIFARE Classic/DESFire/Ultralight (ISO14443A) CSN
- Openpath Proximity
- HID® Proximity
- LenelProx®

### Specifications

|                       |  |
|-----------------------|--|
| Cloud Managed         | Yes  |
| Form                  | Mullion  |
| Color                 | Black  |
| Frequency             | 125 kHz, 13.56 MHz   |
| Openpath Bluetooth    | Yes  |
| NFC                   | Yes  |
| Wave to Unlock        | Yes  |
| Auto Proximity Unlock | Yes  |
| Image Sensor          | 1 / 2.5" 5MP CMOS  |
| Resolution            | 5MP (2592 x 1944)<br>recording at 25 fps                         |
| Video Compression     | H.264, MJPEG   |
| Bit Rate              | CBR, VBR, MBR  |
| Focal Length          | 2.8mm (F1.6)   |
| Field of View         | Horizontal: 109°<br>Vertical: 81°<br>Diagonal: 136°              |
| Min. Illumination     | Color: 2.5 lux<br>B/W: 0.0 lux (IR LED on)                       |
| IR Range              | 9m (29.53ft)   |
| Wide Dynamic Range    | HDR (87dB)   |
| Audio Streaming       | Two-way, full duplex with echo and<br>noise cancellation         |
| Audio Input/Output    | Built-in microphone array,<br>omni-directional; Built-in speaker |
| Audio Encoding        | G.711u, G.711a, G.726  |
| Operating Temperature | -40C (-40F) to 50C (122F)<br>Cold start -25C (-13F)              |
| Storage Temperature   | -40C (-40F) to 50C (122F)  |
| Operating Humidity    | Up to 90% RH non-condensing                                      |
| Standards             | ISO 14443A, Prox   |
| Certification         | FCC, UL 294, CE  |
| Environmental         | IP65   |

### Installation Options

- Surface mounted on wall
- Mounted on gang box
- Installed inside metal enclosure

### Features

- High resolution built-in camera records entry activity
- Smart intercom interface supports multiple configurations
- Supports Openpath's Triple Unlock technology
- Can connect to third-party legacy access control panel
- Indoor/outdoor design
- NDAA/TAA compliant
- Five year warranty

### Installation

- Easy install via a single Ethernet cable
- Wiegand Input/Output for third-party support

| PIGTAIL color       | Name | Description         |
|---------------------|------|---------------------|
| Ethernet            | --   | RJ-45 connector     |
| Black               | GND  | Wiegand RTN         |
| Green               | WD0  | Wiegand Data 0      |
| White               | WD1  | Wiegand Data 1      |
| Blue/White Stripe   | NO   | Relay Normally Open |
| Orange/White Stripe | COM  | Relay Common        |
| Green/Yellow Stripe | GND  | Ground (RTN)        |

Temperature should not exceed -40°C to 60°C (-40°F to 140°F)

### Security

- Fully encrypted communication between mobile app and controller
- Fully encrypted communication between Openpath key cards and reader
- Eliminates the threat of copying or cloning Openpath key cards
- Includes tamper resistant secure storage

### System Compatibility

- Video Intercom Reader Pro works with Openpath Access System including Openpath controllers, cloud management software, and mobile app
- Video Intercom Reader Pro works with legacy access control systems via Mobile Gateway option
- Video Intercom Reader Pro works with third-party VMS software via open video standards, including ONVIF and RTSP

### Dimensions

- With Mullion bracket: 204 x 47 x 37 mm (8.02 x 1.85 x 1.45 in)
- With Standard bracket: 235 x 78 x 37 mm (9.25 x 3.07 x 1.45 in)
- Weight: 384 g (0.85 lbs)

### Power Rating

- Input Voltage: 802.3af PoE (48VDC)
- Power Consumption: 10.8W

### Video Storage

- Edge storage: 10GB eMMC (network failover recording)
- Cloud storage: 30, 60, 90, 180 plans available

### Intercom Functionality

- Initiate and accept calls from the Control Center or Openpath app
- Subscription options available based on number of users

