



KRAMER

VP-428H2

4K60 4:4:4 HDCP 2.2 DisplayPort, HDMI & VGA Auto Switcher/Scaler and PoE Provider over HDBaseT

| VGA/UXGA - 15-pin HD | HDMI | Ethernet - RJ-45 | HDBaseT



VP-428H2 is an HDBaseT 4K transmitter/scaler with HDMI, DP and VGA inputs. VP-428H2 supports HDBaseT tunneling of Ethernet, bidirectional RS-232 and IR signals, as well as PoE to provide power to the HDBaseT receiver. It receives the selected AV signal, up-scales, down scales or bypasses the video, according to the settings selected by the user, and converts it for sending via HDBaseT, together with the tunneled data and PoE

FEATURES

PixPerfect™ Scaling Technology - Kramer's precision pixel mapping and high-quality scaling technology

HDMI 2.0 Compliant

HDCP 2.2 Compliant

HDBaseT Certified

System Range - For the HDBaseT output, extended reach of up to 100m (330ft) using Kramer recommended cables

Provides Power (PoE) on HDBaseT Output to Compatible Devices

Max. Resolutions - Input: 4K@60Hz (4:4:4); Output: 4K@60Hz (4:2:0)

Max. VGA Resolution - 1920 x 1200 @60Hz

Built-in ProcAmp - Color, hue, sharpness, noise, contrast and brightness are set individually for each input

Constant Output Sync - No output disruption while switching between inputs when no video is detected

Audio - Unbalanced stereo and embedded audio

Auto Input Switching - Last connected & auto-scan, selectable

HDBaseT Tunneling - Supports full HDBaseT tunneling of Ethernet and RS-232 data

Non-Volatile Memory - Saves final settings

Flexible Control Options - Front panel push buttons, RS-232, OSD (on-screen display) menu with front panel navigation buttons



TECHNICAL SPECIFICATIONS

Inputs

1 HDMI On a female HDMI connector

1 PC On a 15-pin HD connector

1 Stereo Analog Unbalanced Audio On a 3.5mm mini jack

1 IR On a 3.5mm mini jack

Outputs

1 IR On a 3.5mm mini jack

Ports

1 USB On a female USB-A connector

1 DATA RS-232 On a 3-pin terminal block for serial link extension

PRODUCT DIMENSION: 18.75cm x 14.50cm x 2.54cm (7.38" x 5.71" x 1.00") W, D, H

PRODUCT WEIGHT: 1.5kg (3.4lbs) approx

SHIPPING DIMENSION: 35.10cm x 21.20cm x 7.20cm (13.82" x 8.35" x 2.83") W, D, H

SHIPPING WEIGHT: 1.1kg (2.4lbs) approx

Ports

Video

Max. Input Resolution 4K@60Hz (4:4:4)

Max. Output Resolution 4K@60Hz (4:2:0)

Standards Compliance HDMI 2.0 and HDCP 2.2

Switching Time Between Inputs 2 to 3 seconds

Video Latency 2 to 3 frames

Input Resolutions 640x350@60/70/85Hz, 640x400@70/85Hz, 640x480@57/60/66/72/85Hz, 720x400@70/85Hz, 720x480@60i/60p/60Hz, 720x576@50i/50p/60Hz, 800x600@56/60/72/75/85Hz, 832x624@75Hz, 848x480@59/60Hz, 864x648@60Hz, 1024x768@43i/60/70/75/85Hz, 1152x864@60/70/75/85Hz, 1152x870@60/75Hz, 1280x720@25p/30p/50p/60p/75Hz, 1280x768@50/60 (RB)/60/75/85Hz, 1280x800@59/60/75/85Hz, 1280x960@60/75/85Hz, 1280x1024@59/60/72/75/76/85Hz, 1360x768@60Hz, 1366x768@60Hz, 1400x1050@59/60/75Hz, 1440x900@60 (RB)/60/75/85Hz, 1600x900@60 (RB)/60/75Hz, 1600x1024@60/75Hz, 1600x1200@51/59/60/65/70/75Hz, 1680x1050@59/60/75Hz, 1920x1200@59/60/65/75Hz, 1920x1080@50i/60i/24p/25p/30p/50p/60p/60Hz, 920x1080@60s, 1920x1080@50vesa, 3840x2160@24p/25p/30p/50p/50p (420)/60p/60p (420)/60p (RB), 4096x2160@24p/25p/30p/50p/50p (420)/60p/60p (420)

Output Resolutions Native, 640x480@60Hz, 720x480P@60Hz, 720x576P@50Hz, 800x600@60Hz, 1024x768@60Hz, 1280x720@60Hz, 1280x768@60Hz, 1280x800@60Hz, 1280x1024@60Hz, 1360x768@60Hz, 1400x1050@60Hz, 1440x900@60Hz, 1600x1200@60Hz, 1680x1050@60Hz, 1920x1080@60Hz, 1920x1200@60Hz, 1280x720P@50/60Hz, 1920x1080P@24/25/30/50/60Hz, 4K@24/25/30Hz, 4K2K(4:2:0)@50/60Hz

Power

Consumption 48V DC, 1.36A

Enclosure

Type Aluminum

Environmental Conditions

Storage Temperature -40° to +70°C (-40° to 158°F)

Humidity 10% to 90%, RHL non-condensing

Accessories

Optional RK-T2B rack adapter

