

VM-3AN

1:3 Balanced Stereo Audio Distribution Amplifier



The VM-3AN is a high-performance distribution amplifier for balanced stereo audio signals. The unit takes one stereo input and distributes the signal to three identical outputs

FEATURES

S/N Ratio - 90dB L & R Level (Gain) Controls



TECHNICAL SPECIFICATIONS

INPUT: 1 balanced stereo audio on a 5-pin terminal block

OUTPUTS: 3 balanced stereo audio on 5-pin terminal blocks

MAX. OUTPUT

LEVEL:

Audio: 18.5Vpp

BANDWIDTH (-3dB): >100 kHz

S/N RATIO: 90dB @1kHz

CONTROL: Output level control: -77 to +6dB, R+/-, L+/- channels

AUDIO THD + NOISE: 0.008%

AUDIO 2d 0.001% HARMONIC:

POWER 12V DC, 89mA

CONSUMPTION:

INCLUDED ACCESSORIES:

Product Dimensions

Power supply

Product Weight 0.2kg (0.4lbs) approx

Shipping Dimensions $15.70 \, \text{cm} \times 12.00 \, \text{cm} \times 8.70 \, \text{cm} (6.18" \times 4.72" \times 3.43") \, \text{W, D, H}$

12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H

Shipping Weight 0.5kg (1.1lbs) approx

